


Service Manual

Plasma Television

Model No. **TH-P50ST60A**
TH-P50ST60D
TH-P50ST60M
TH-P50ST60Z

GPF16D-A Chassis



⚠ WARNING

This service information is designed for experienced repair technicians only and is not designed for use by the general public. It does not contain warnings or cautions to advise non-technical individuals of potential dangers in attempting to service a product. Products powered by electricity should be serviced or repaired only by experienced professional technicians. Any attempt to service or repair the product or products dealt with in this service information by anyone else could result in serious injury or death.

IMPORTANT SAFETY NOTICE

There are special components used in this equipment which are important for safety. These parts are marked by **⚠** in the Schematic Diagrams, Circuit Board Diagrams, Exploded Views and Replacement Parts List. It is essential that these critical parts should be replaced with manufacturer's specified parts to prevent shock, fire or other hazards. Do not modify the original design without permission of manufacturer.

Panasonic®

© Panasonic Corporation 2013.
Unauthorized copying and distribution is a violation of law.

TABLE OF CONTENTS

	PAGE
1 Safety Precautions	3
1.1. General Guidelines	3
1.2. Touch-Current Check	3
2 Warning	4
2.1. Prevention of Electrostatic Discharge (ESD) to Electrostatically Sensitive (ES) Devices	4
2.2. About lead free solder (PbF)	5
3 Service Navigation	6
3.1. PCB Layout	6
4 Specifications	7
5 Technical Descriptions	9
5.1. Specification of KEY for DTCP-IP, One-to- One, Widevine and Netflix	9
5.2. USB HDD Recording	9
5.3. Panel-Type setting	9
6 Service Mode	10
6.1. How to enter into Service Mode	10
6.2. Option - Mirror	12
6.3. Service tool mode	12
6.4. DRV Check - USB HDD Check	13
6.5. Hotel mode	13
6.6. Data Copy by USB Memory	14
7 Troubleshooting Guide	17
7.1. Check of the IIC bus lines	17
7.2. Power LED Blinking timing chart	18
7.3. No Power	19
7.4. No Picture	19
7.5. Local screen failure	20
8 Service Fixture & Tools	21
8.1. SC jig	21
9 Disassembly and Assembly Instructions	22
9.1. Disassembly Flow Chart for the Unit	22
9.2. Disassembly Procedure for the Unit	23
10 Measurements and Adjustments	29
10.1. Adjustment	29
11 Block Diagram	31
11.1. Main Block Diagram	31
11.2. Block (1/4) Diagram	32
11.3. Block (2/4) Diagram	33
11.4. Block (3/4) Diagram	34
11.5. Block (4/4) Diagram	35
12 Wiring Connection Diagram	37
12.1. Caution statement	37
12.2. Wiring (1)	37
12.3. Wiring (2)	38
12.4. Wiring (3)	38

1 Safety Precautions

1.1. General Guidelines

1. When conducting repairs and servicing, do not attempt to modify the equipment, its parts or its materials.
2. When wiring units (with cables, flexible cables or lead wires) are supplied as repair parts and only one wire or some of the wires have been broken or disconnected, do not attempt to repair or re-wire the units. Replace the entire wiring unit instead.
3. When conducting repairs and servicing, do not twist the Fasten connectors but plug them straight in or unplug them straight out.
4. When servicing, observe the original lead dress. If a short circuit is found, replace all parts which have been overheated or damaged by the short circuit.
5. After servicing, see to it that all the protective devices such as insulation barriers, insulation papers shields are properly installed.
6. After servicing, make the following leakage current checks to prevent the customer from being exposed to shock hazards.

1.2. Touch-Current Check

1. Plug the AC cord directly into the AC outlet. Do not use an isolation transformer for this check.
2. Connect a measuring network for touch currents between each exposed metallic part on the set and a good earth ground such as a water pipe, as shown in Figure 1.
3. Use Leakage Current Tester (Simpson 228 or equivalent) to measure the potential across the measuring network.
4. Check each exposed metallic part, and measure the voltage at each point.
5. Remove the AC plug in the AC outlet and repeat each of the above measure.
6. The potential at any point (TOUCH CURRENT) expressed as voltage U_1 and U_2 , does not exceed the following values:

For a. c.: $U_1 = 35$ V (peak) and $U_2 = 0.35$ V (peak);

For d. c.: $U_1 = 1.0$ V,


Note:

The limit value of $U_2 = 0.35$ V (peak) for a. c. and $U_1 = 1.0$ V for d. c. correspond to the values 0.7 mA (peak) a. c. and 2.0 mA d. c.

The limit value $U_1 = 35$ V (peak) for a. c. correspond to the value 70 mA (peak) a. c. for frequencies greater than 100 kHz.

7. In case a measurement is out of the limits specified, there is a possibility of a shock hazard, and the equipment should be repaired and rechecked before it is returned to the customer.

Measuring network for TOUCH CURRENTS



Resistance values in ohms (Ω)

V: Voltmeter or oscilloscope
(r.m.s. or peak reading)

Input resistance: ≥ 1 M Ω

Input capacitance: ≤ 200 pF

Frequency range: 15 Hz to 1 MHz and d.c. respectively

NOTE - Appropriate measures should be taken to obtain the correct value in case of non-sinusoidal waveforms.

Figure 1

2 Warning

2.1. Prevention of Electrostatic Discharge (ESD) to Electrostatically Sensitive (ES) Devices

Some semiconductor (solid state) devices can be damaged easily by static electricity. Such components commonly are called Electrostatically Sensitive (ES) Devices. Examples of typical ES devices are integrated circuits and some field-effect transistors and semiconductor [chip] components. The following techniques should be used to help reduce the incidence of component damage caused by electrostatic discharge (ESD).

1. Immediately before handling any semiconductor component or semiconductor-equipped assembly, drain off any ESD on your body by touching a known earth ground. Alternatively, obtain and wear a commercially available discharging ESD wrist strap, which should be removed for potential shock reasons prior to applying power to the unit under test.
2. After removing an electrical assembly equipped with ES devices, place the assembly on a conductive surface such as aluminum foil, to prevent electrostatic charge buildup or exposure of the assembly.
3. Use only a grounded-tip soldering iron to solder or unsolder ES devices.
4. Use only an anti-static solder removal device. Some solder removal devices not classified as [anti-static (ESD protected)] can generate electrical charge sufficient to damage ES devices.
5. Do not use freon-propelled chemicals. These can generate electrical charges sufficient to damage ES devices.
6. Do not remove a replacement ES device from its protective package until immediately before you are ready to install it. (Most replacement ES devices are packaged with leads electrically shorted together by conductive foam, aluminum foil or comparable conductive material).
7. Immediately before removing the protective material from the leads of a replacement ES device, touch the protective material to the chassis or circuit assembly into which the device will be installed.

Caution

Be sure no power is applied to the chassis or circuit, and observe all other safety precautions.

8. Minimize bodily motions when handling unpackaged replacement ES devices. (Otherwise ham less motion such as the brushing together of your clothes fabric or the lifting of your foot from a carpeted floor can generate static electricity (ESD) sufficient to damage an ES device).

2.2. About lead free solder (PbF)

Note: Lead is listed as (Pb) in the periodic table of elements.

In the information below, Pb will refer to Lead solder, and PbF will refer to Lead Free Solder.

The Lead Free Solder used in our manufacturing process and discussed below is (Sn+Ag+Cu).


That is Tin (Sn), Silver (Ag) and Copper (Cu) although other types are available.

This model uses Pb Free solder in it's manufacture due to environmental conservation issues. For service and repair work, we'd suggest the use of Pb free solder as well, although Pb solder may be used.

PCBs manufactured using lead free solder will have the PbF within a leaf symbol **PbF** stamped on the back of PCB.

Caution

- Pb free solder has a higher melting point than standard solder. Typically the melting point is 50 ~ 70 °F (30~40 °C) higher. Please use a high temperature soldering iron and set it to 700 ± 20 °F (370 ± 10 °C).
- Pb free solder will tend to splash when heated too high (about 1100 °F or 600 °C). If you must use Pb solder, please completely remove all of the Pb free solder on the pins or solder area before applying Pb solder. If this is not practical, be sure to heat the Pb free solder until it melts, before applying Pb solder.
- After applying PbF solder to double layered boards, please check the component side for excess solder which may flow onto the opposite side. (see figure below)



Suggested Pb free solder


There are several kinds of Pb free solder available for purchase. This product uses Sn+Ag+Cu (tin, silver, copper) solder.

However, Sn+Cu (tin, copper), Sn+Zn+Bi (tin, zinc, bismuth) solder can also be used.

0.3mm X 100g	0.6mm X 100g	1.0mm X 100g

3 Service Navigation

3.1. PCB Layout



Board Name	Function
P	Power Supply
A	Main AV input, processing
K	Remote receiver, Power LED, C.A.T.S sensor
C1	Data Driver (Lower Right)
C2	Data Driver (Lower Center)
C3	Data Driver (Lower Left)
SC	Scan Drive
SS	Sustain Drive
SS2	Sustain out (Lower)
SU	Scan out (Upper) Non serviceable. SU-Board should be exchanged for service.
SD	Scan out (Lower) Non serviceable. SD-Board should be exchanged for service.

4 Specifications

Power (A/Z)

Rating	AC 220-240 V, 50 / 60 Hz 2.1 A
Normal (Home) mode	122 W
Standby power consumption	0.3 W

Power (D/M)

Power Source	AC 220 - 240 V, 50 / 60 Hz
Rating	390 W
Standby power consumption	0.3 W

Visible screen size (diagonal)

127 cm

Display resolution

1,920 (W) × 1,080 (H)

Panel

Plasma Display

Dimensions (W × H × D)

1,170 mm × 751 mm × 295 mm (With Pedestal)
1,170 mm × 697 mm × 49 mm (TV only)

Mass

25.5 kg Net (With Pedestal)
22.5 kg Net (TV only)

Connection terminals

AV IN (COMPONENT / VIDEO)

VIDEO	RCA PIN Type × 1	1.0 V [p-p] (75 Ω)
AUDIO L - R	RCA PIN Type × 2	0.5 V [rms]
Y	1.0 V [p-p] (including synchronization)	
P _B /C _B , P _R /C _R	± 0.35 V [p-p]	
HDMI 1 / 2 / 3 input	TYPE A Connectors	

HDMI 1 / 3 : 3D, Content Type, Deep Colour, x.v.Colour™

HDMI 2 : 3D, Content Type, Audio Return Channel, Deep Colour, x.v.Colour™

- This TV supports "HDAVI control 5" function.

Card slot SD Card slot × 1

ETHERNET 10BASE-T / 100BASE-TX

USB 1 / 2 USB 2.0 DC 5 V, Max. 500 mA

DIGITAL AUDIO OUT PCM / Dolby Digital / DTS, Fibre optic

Sound

Speaker Speaker × 2, Woofer (φ 75 mm) × 1

Audio output 20 W (5 W + 5 W + 10 W)

Receiving systems / Band name (A/Z)

Digital TV 7 MHz VHF/UHF (Australia) free-to-air TV broadcast reception

8 MHz UHF (New Zealand) free-to-air TV broadcast reception

Reception of Off air broadcasts

PAL B/G Playback of NTSC tape from some PAL Video recorders (VCR)

PAL 60 Hz Playback from M.NTSC Video recorders (VCR)

M.NTSC Playback from NTSC Video recorders (VCR)

NTSC

Receiving systems / Band name (D/M)

17 Systems		Function	17 Systems		Function
1	PAL B, G, H		8	NTSC 4.43/5.5 MHz	
2	PAL I	Reception of broadcast	9	NTSC 4.43/6.0 MHz	
3	PAL D, K	transmissions and	10	NTSC 4.43/6.5 MHz	
4	SECAM B, G	Playback from	11	NTSC 3.58/5.5 MHz	Playback from Special VCR's or
5	SECAM D, K	Video Cassette	12	NTSC 3.58/6.0 MHz	DVD
6	SECAM K1	Tape Recorders	13	NTSC 3.58/6.5 MHz	
7	NTSC M (NTSC 3.58/4.5 MHz)		14	SECAM I	
			15	PAL 60 Hz/5.5 MHz	Playback from Special Disc
			16	PAL 60 Hz/6.0 MHz	Players and Special
			17	PAL 60 Hz/6.5 MHz	VCR's or DVD

Receiving Channels (D/M)

VHF BAND

2-12 (PAL/SECAM B, K1) 0-12 (PAL B AUST.)

1-9 (PAL B N.Z.)

1-12 (PAL/SECAM D)

1-12 (NTSC M Japan)

2-13 (NTSC M USA)

UHF BAND

21-69 (PAL G, H, I/SECAM G, K, K1)

28-69 (PAL B AUST.) 13-57 (PAL D, K)

13-62 (NTSC M Japan)

14-69 (NTSC M USA)

CATV

S1-S20 (OSCAR)

1-125 (USA CATV)

C13-C49 (JAPAN)

S21-S41 (HYPER)

Z1-Z37 (CHINA)

5A, 9A (AUST.)

VHF / UHF

Aerial - Rear

Operating Conditions

Built-in wireless LAN

Standard compliance and Frequency range^{*1}

Temperature: 0 °C - 40 °C (D/M) 0 °C - 35 °C (A/Z)
Humidity: 20 % - 80 % RH (non-condensing)

Security

Bluetooth wireless technology^{*2}

Standard Compliance

IEEE 802.11a/n

5.15 GHz - 5.35 GHz, 5.47 GHz - 5.85 GHz

Frequency Range

IEEE 802.11b/g/n

2.40 GHz - 2.4835 GHz

WPA2-PSK (TKIP/AES) WPA-PSK (TKIP/AES) WEP (64 bit/128 bit)

^{*1}: The frequency and channel differ depending on the country.

^{*2}: Not all the Bluetooth compatible devices are available with this TV. Up to 5 devices can be used simultaneously (except the 3D Eyewear).

■ 3D Eyewear

Dimensions (W × H × D)

164.7 mm × 41.0 mm × 170.7 mm

Mass

Approx. 34 g

Lens type

Liquid Crystal Shutter

Usage temperature range

0 °C - 40 °C

Battery

Coin-shaped lithium battery CR2025

Operation time: Approx. 75 hours in continuous use of the battery made by Panasonic

Materials

Main body: Resin

Lens section: Liquid crystal glass

- 3D Eyewear uses Bluetooth wireless technology.

Note

- Design and Specifications are subject to change without notice. Mass and Dimensions shown are approximate.
- For the information of the open source software, refer to [eHELP] (Support > Licence).

5 Technical Descriptions

5.1. Specification of KEY for DTCP-IP, One-to-One, Widevine and Netflix

5.1.1. General information:

1. NAND Flash (IC8900) for spare parts has the seed of KEY for each.
2. The final KEY data will be generated by Main IC (IC8000) when SELF CHECK was done and are stored in both Main IC (IC8000) and NAND Flash (IC8900).

Four KEY are not generated for all models.

The necessary KEY are only generated and stored depend on the feature of models.

5.1.2. Replacement of ICs:

When Main IC (IC8000) is replaced, NAND Flash (IC8900) should be also replaced with new one the same time.

When NAND Flash (IC8900) is replaced, Main IC (IC8000) is not necessary to be replaced the same time.

After the replacement of IC, SELF CHECK should be done to generate the final KEY data.

How to SELF CHECK: While pressing [VOLUME (-)] button on the main unit, press [MENU] button on the remote control for more than 3 seconds.

TV will be forced to the factory shipment setting after this SELF CHECK.

5.1.3. Model and Keys:

Model No.	Keys			
	One-to-One (For USB Rec.)	DTCP-IP	WIDEVINE	Netflix
TH-P50ST60A	Yes	None	Yes	Yes
TH-P50ST60D/M	None	None	Yes	Yes
TH-P50ST60Z	Yes	Yes	Yes	Yes

5.2. USB HDD Recording

5.2.1. General information:

Digital TV programmes can be recorded in USB HDD.

A One-to-One key generated in A-board by SELF CHECK binds TV and USB-HDD for communication.

That key is only one key for them. If the key is difference, TV can not access USB-HDD.

Caution:

New key will be generated by following SELF CHECK and previous TV programmes recorded in USB HDD will not be viewed.

SELF CHECK: While pressing [VOLUME (-)] button on the main unit, press [MENU] button on the remote control for more than 3 seconds.

5.3. Panel-Type setting

Panel-Type setting is required after exchange the A-board.

A-board for spare parts is common use for different inch size in same series.

Go into Service Mode and confirm/select Panel-Type in OPTION to correct inch size.

6 Service Mode

6.1. How to enter into Service Mode

6.1.1. Purpose


After exchange parts, check and adjust the contents of adjustment mode.

While pressing [VOLUME (-)] button of the main unit, press [i] button of the remote control three times within 2 seconds.

Note:

Service Mode can not be entered when 3D signal input.

Input 2D signal to enter Service Mode.



6.1.2. Key command

[1] button...Main items Selection in forward direction

[2] button...Main items Selection in reverse direction

[3] button...Sub items Selection in forward direction

[4] button...Sub items Selection in reverse direction

[VOL] button...Value of sub items change in forward direction (+), in reverse direction (-)

6.1.3. How to exit

Switch off the power with the [POWER] button on the main unit or the [POWER] button on the remote control.

6.1.4. Contents of adjustment mode

- Value is shown as a hexadecimal number.
- Preset value differs depending on models.
- After entering the adjustment mode, take note of the value in each item before starting adjustment.

Main item	Sub item	Sample Data	Remark
ADJUST	CONTRAST	000	
	COLOR	3C	
	TINT	00	
	SUB-BRT	800	
	H-POS	0	
	H-AMP	0	
	V-POS	0	
	V-AMP	0	
WB-ADJ	R-CUT	80	
	G-CUT	80	
	B-CUT	80	
	R-DRV	FF	
	G-DRV	FF	
	B-DRV	E1	
	ALL-CUT	80	
	ALL-DRV	FF	
OPTION	Panel-Type	50FHD	Factory Preset
	Boot	ROM	
	STBY-SET	00	
	EMERGENCY	ON	
	CLK MODE	00	
	CLOCK	000	
	Y/C Delay		
	OPT 1	00010000	
	OPT 2	00100010	
	OPT 3	00000001	
	OPT 4	00010000	
	EDID-CLK	HIGH	
	MIRROR	00 (See Option-Mirror)	
	AMR-SELECT	OFF	
VSUS		LOW	See Vsus selection
AGING	ALL WHITE		Built-in test patterns can be displayed.
	MIDDLE BLUE WITH MAGENTA OUTSIDE FRAME		
	MIDDLE STEP GREEN		
	MIDDLE STEP RED		
	LOW STEP WHITE		
	ALL BLUE		
	ALL GREEN		
	ALL RED		
	WHITE DIAGONAL STRIPE		
	RED DIAGONAL STRIPE		
	GREEN DIAGONAL STRIPE		
	BLUE DIAGONAL STRIPE		
	A-ZONE & B-ZONE		
	1% WINDOW		
	COLOR BAR		
	9 POINTS BRIGHT MEASURE		
	2 DOT OUTSIDE FRAME		
	DOUBLE FIXED 1% WINDOW		
	VERTICAL LINE SCROLL		
	ON/OFF		
	R/G/B/W ROTATION WITH COUNT DISPLAY		
	HALF FIXED ALL WHITE		
	ALL WHITE WITH COUNT DISPLAY		
SRV-TOOL		00	See Service tool mode
DRV CHECK	USBHDD CHECK	00	See DRV Check-USBHDD Check

6.2. Option - Mirror

Picture can be reversed left and right or up and down.

00 : Default (Normal picture is displayed)

01 : Picture is reversed left and right.

02 : Picture is reversed up and down.

00



01



02



Hint : If the defective symptom (e.g. Vertical bar or Horizontal bar) is moved by selection of this mirror, the possible cause is in A-board.

6.3. Service tool mode

6.3.1. How to access

1. Select [SRV-TOOL] in Service Mode.
2. Press [OK] button on the remote control.

SRV-TOOL		
Display of TD2Microcode version →	TD2Microcode:00000000	
Display of Flash ROM maker code →	Flash ROM : 98 - DC	
Display of SOS History →	PTCT : 00 . 00 . 00 . 00 . 00 .	Time 00000:40 Count 0000001 POWER ON TIME/COUNT Press [MUTE] button (3 sec)

6.3.2. Display of SOS History

SOS History (Number of LED blinking) indication.

From left side; Last SOS, before Last, three occurrence before, 2nd occurrence after shipment, 1st occurrence after shipment.

This indication except 2nd and 1st occurrence after shipment will be cleared by [Self-check indication and forced to factory shipment setting].

6.3.3. POWER ON TIME/COUNT

Note : To display TIME/COUNT menu, highlight position, then press MUTE for 3 sec.

Time : Cumulative power on time, indicated hour : minute by decimal

Count : Number of ON times by decimal


Note : This indication will not be cleared by either of the self-checks or any other command.

6.3.4. Exit

Disconnect the AC cord from wall outlet or switch off the power with [Power] button on the main unit.

6.4. DRV Check - USB HDD Check

1. Select [DRV Check - USBHDD Check] in Service Mode.
2. Press [OK] button on the remote control for more than 3 seconds.



6.5. Hotel mode

1. Purpose
Restrict a function for hotels.
2. Access command to the Hotel mode setup menu
In order to display the Hotel mode setup menu:
While pressing [VOLUME (-)] button of the main unit,
press [AV] button of the remote control three times within
2 seconds.

Then, the Hotel mode setup menu is displayed.

Hotel Mode	
Hotel Mode	Off
Initial INPUT	Off
Initial POS	Off
Initial VOL Level	Off
Maximum VOL Level	100
Button Lock	Off
Remote Lock	Off
Private Information	Keep

Select
Change
RETURN

3. To exit the Hotel mode setup menu
Switch off the power with the [POWER] button on the main unit or the [POWER] button on the remote control.
4. Explain the Hotel mode setup menu

Item	Function
Hotel Mode	Select hotel mode On/Off
Initial INPUT	Select input signal modes. Set the input, when each time power is switched on. Selection : Off,Analogue TV,Digital TV,AV,HDMI1,HDMI2, HDMI3 • Off: give priority to a last memory.
Initial POS	Select programme number. Selection : Off/0 to 99 • Off: give priority to a last memory
Initial VOL Level	Adjust the volume when each time power is switched on. Selection/Range : Off/0 to 100 • Off: give priority to a last memory
Maximum VOL Level	Adjust maximum volume. Range : 0 to 100
Button Lock	Select local key conditions. Selection : Off/SETUP/MENU • Off: altogether valid • SETUP: only F-key is invalid (Tuning guide (menu) can not be selected.) • MENU: only F-key is invalid (only Volume/Mute can be selected.)
Remote Lock	Select remote control key conditions. Selection : Off/SETUP/MENU • Off: altogether valid • SETUP: only Setup menu is invalid • MENU: Picture/Sound/Setup menu are invalid
Private Information	Select private information for VIERA Cast is Keep or Reset if Hotel mode is set to [On] when TV power on. Selection : Keep/Reset • Keep: private information for VIERA Cast is keep • Reset: private information for VIERA Cast is reset

6.6. Data Copy by USB Memory


Note:

SD card can not be used for Data Copy.

6.6.1. Purpose


(a) Board replacement (Copy the data when exchanging A-board):

When exchanging A-board, the data in original A-board can be copied to USB Memory and then copy to new A-board.



(b) Hotel (Copy the data when installing a number of units in hotel or any facility):

When installing a number of units in hotel or any facility, the data in master TV can be copied to USB Memory and then copy to other TVs.



6.6.2. Preparation

Make pwd file as startup file for (a) or (b) in a empty USB Memory.

1. Insert a empty USB Memory to your PC.
2. Right-click a blank area in a USB Memory window, point to New, and then click text document. A new file is created by default (New Text Document.txt).
3. Right-click the new text document that you just created and select rename, and then change the name and extension of the file to the following file name for (a) or (b) and press ENTER.

File name:

- (a) For Board replacement : boardreplace.pwd
- (b) For Hotel : hotel.pwd

Note:

Please make only one file to prevent the operation error.

No any other file should not be in USB Memory.


6.6.3. Data copy from TV set to USB Memory

1. Turn on the TV set.
2. Insert USB Memory with a startup file (pwd file) to USB terminal.
On-screen Display will be appeared according to the startup file automatically.
3. Input a following password for (a) or (b) by using remote control.
 - (a) For Board replacement : 2770
 - (b) For Hotel : 4850
4. After the completion of copying to USB Memory, remove USB Memory from TV set.
5. Turn off the TV set.

Note:

Following new folder will be created in USB Memory for data from TV set.

- (a) For Board replacement : user_setup
- (b) For Hotel : hotel




6.6.4. Data copy from USB Memory to TV set

1. Turn on the TV set.
2. Insert USB Memory with Data to USB terminal.
On-screen Display will be appeared according to the Data folder automatically.
3. Input a following password for (a) or (b) by using remote control.
 - (a) For Board replacement : 2771
 - (b) For Hotel : 4851
4. Data will be copied from USB Memory to TV set.
5. After the completion of copying to USB Memory, remove USB Memory from TV set.
 - (a) For Board replacement : Data will be deleted after copying (Limited one copy).
 - (b) For Hotel : Data will not be deleted and can be used for other TVs.
6. Turn off the TV set.

Note:

1. Depending on the failure of boards, function of Data copy for board replacement does not work.
2. This function can be effective among the same model numbers.



7 Troubleshooting Guide

Use the self-check function to test the unit.

1. Checking the IIC bus lines
2. Power LED Blinking timing

7.1. Check of the IIC bus lines

7.1.1. How to access

7.1.1.1. Self-check indication only:

Produce TV reception screen, and while pressing [VOLUME (-)] button on the main unit, press [OK] button on the remote control for more than 3 seconds.


7.1.1.2. Self-check indication and forced to factory shipment setting:

Caution:

New key will be generated and previous TV programmes recorded in USB HDD will not be viewed. (See USB HDD Recording) (Z only)

Produce TV reception screen, and while pressing [VOLUME (-)] button on the main unit, press [MENU] button on the remote control for more than 3 seconds.

7.1.2. Screen display



7.1.3. Check Point

Confirm the following parts if NG was displayed.

DISPLAY	Check Ref. No.	Description	Check Point
H14TUN	TU6705	TUNER	A-BOARD
H90STBY	IC8000	PARAGON (STM)	A-BOARD
H91MEM2	IC8900	NAND FLASH	A-BOARD
H38PANEL		PLASMA PANEL	A-BOARD/PLASMA PANEL
H38PD6	IC9300	PD6H	A-BOARD
H07TEMP	IC2001	TEMP SENSOR	A-BOARD
H17LAN		LAN	A-BOARD
H00FE	IC6803	Front End	A-BOARD
H97ID2		ID2	A-BOARD
H45BT		BLUETOOTH	A-BOARD/BLUETOOTH
H42WiFi		WiFi	A-BOARD/WiFi
H21DSP	IC4900	AUDIO AMP	A-BOARD

7.1.4. Exit

Disconnect the AC cord from wall outlet or press the [POWER] button on the main unit for 3 seconds to turn off and then turn on automatically.

7.2. Power LED Blinking timing chart

1. Subject

Information of LED Flashing timing chart.

2. Contents

When an abnormality has occurred the unit, the protection circuit operates and reset to the stand by mode. At this time, the defective block can be identified by the number of blinks of the Power LED on the front panel of the unit.

Blinking Times	Contents	Check point
1	Panel information SOS PD Start SOS	-
2	P15V SOS	A-Board P-Board
6	Driver SOS1 (SC Energy recovery circuit) (A-SC FPC DET)	SC-Board A-SC FPC
7	Driver SOS2 (SU/SD Connector DET) (SU/SD Scan and Logic IC)	SU-Board SD-Board *
8	Driver SOS3 (SS FPC DET) (SS Energy recovery circuit)	SS-Board SS2-Board SS FPC SS2 FPC
9	Discharge Control SOS	A-Board
10	Sub 3.3V SOS Tuner power SOS	A-Board SC-Board SS-Board P-Board
12	Sound SOS	A-Board Speaker Woofer
13	Emergency SOS	A-Board


* Use SC jig to isolate the board.

7.3. No Power


First check point

There are following 3 states of No Power indication by power LED.

1. No lit
2. Green is lit then turns red blinking a few seconds later. (See Power LED Blinking timing chart)
3. Only red is lit.



7.4. No Picture



7.4.1. Drive circuits LED indicator

Check that the following LEDs on the SC and SS-Board.

Power recovery LED

	LED for check
SC	D16583
SS	D16254A

7.5. Local screen failure

Plasma display may have local area failure on the screen. Fig-1 is the possible defect P.C.B. for each local area.




Fig-1

8 Service Fixture & Tools

8.1. SC jig

Purpose:

To find the failure board (SC or SU/SD) when the power LED is blinking 7 times.

SC jig:

Jumper connector to connect to SC50 connector on SC board

Part number:


TZSC09187

How to use:

Caution: Remove SC jig from SC board after inspection.

1. Remove the 2 VFG screws from SU and SD board.
2. Remove all connector between SC board and SU/SD board to isolate SC board from both SU and SD board electrically.
Note: The board will be damaged if all connector is not removed (for example; remove connector only for SU board and stay connecting with SD board. The board will be damaged.)
3. Connect SC jig to connector SC50 at left bottom side of SC board
4. Turn on the TV/Display Unit and confirm the power LED blinking.
LED blinking: Possible cause of failure is in SC board
No LED blinking (Lighting or no lighting): Possible cause of failure is in SU or SD board
5. After inspection, turn off the TV/Display Unit and wait a few minutes to discharge.
6. Remove SC jig from SC board.

Remark: This SC jig can be used for all 2013 Plasma TV and Plasma Display.




9 Disassembly and Assembly Instructions

9.1. Disassembly Flow Chart for the Unit

This is a disassembly chart.


When assembling, perform this chart conversely.



9.2. Disassembly Procedure for the Unit

9.2.1. Remove the Pedestal stand


1. Remove the Plasma panel section from the servicing stand and lay on a flat surface such as a table (covered by a soft cloth) with the Plasma panel surface facing downward.
2. Remove the screws ($\times 4 \rightarrow$)
3. Slide the Pedestal stand to the downside and remove the Pedestal stand.



Pedestal stand ↓ downside

9.2.2. Remove the Bottom cover


1. Remove the screws ($\times 4 \rightarrow$) and remove the Bottom cover.



Bottom cover

9.2.3. Remove the AC cord clamper B


1. Remove the screws ($\times 2 \rightarrow$) and remove the AC cord clamper B.



AC cord clamper B

9.2.4. Remove the Wi-Fi module


1. Remove the screw ($\times 1 \rightarrow$) and remove the Wi-Fi module.



Wi-Fi module


9.2.5. Remove the Bluetooth module

1. Remove the screw ($\times 1 \rightarrow$) and remove the Dongle cover.



Dongle cover


2. Remove the Pin guides ($\times 2 \rightarrow$) and disconnect the BT connector.
3. Remove the Bluetooth module.



Bluetooth module

9.2.6. Remove the Rear cover

1. Remove the screws ($\times 27 \rightarrow, \times 2 \rightarrow$).
2. Remove the M8 caps ($\times 4 \rightarrow$).
3. Remove the Rear cover.




→ (1) THEC1509
→ (2) THEL0239
→ (3) TKKL5493

9.2.7. Remove the P-Board

Caution:


To remove P.C.B. wait 1 minute after power was off for discharge from electrolysis capacitors.

1. Unlock the hooks and the tapes to free the cables
2. Disconnect the connectors (P2, P6, P11 and P35).
3. Remove the screws ($\times 5 \rightarrow$, $\times 1 \rightarrow$, $\times 1 \rightarrow$) and remove the P-Board.




9.2.8. Remove the A-Board

1. Unlock the hooks and the tapes to free the cables.
2. Disconnect the connectors (A1, A6 and A12).
3. Disconnect the USB cable (JK8605).
4. Disconnect the flexible cables (A20, A31, A32 and A33).
5. Remove the screws ($\times 3 \rightarrow$).
6. Remove the Side shield metal and the Bottom shield metal.
7. Remove the A-Board.




8. Remove the screws ($\times 2 \rightarrow$).

9. Remove the Heatsink (bottom) and the Heat rubber.




9.2.9. Remove the Control unit assy

1. Unlock the tape to free the cables.
2. Disconnect the connector (C14).
3. Remove the claws ($\times 2 \rightarrow$) and remove the Control unit assy.




9.2.10. Remove the Speaker SQs

1. Unlock the hooks and the tapes to free the cables.
2. Disconnect the Relay connector.
3. Remove the screws ($\times 2 \rightarrow$ each) and remove the Speaker SQs (L, R).




9.2.11. Remove the Woofer

1. Unlock the hooks and the tapes to free the cables.
2. Disconnect the Relay connector.
3. Remove the screws ($\times 3 \rightarrow$) and remove the Woofer.




9.2.12. Remove the SU-Board

1. Disconnect the flexible cables (SU1, SU2, SU3, SU4 and SU5) connected to the SU-Board.
2. Disconnect the flexible cable (SU11-SD11) and the bridge connector (SC41-SU41).
3. Remove the screws ($\times 2 \rightarrow$, $\times 1 \rightarrow$) and remove the SU-Board.




9.2.13. Remove the SD-Board

1. Disconnect the flexible cables (SD1, SD2, SD3, SD4 and SD5) connected to the SD-Board.
2. Disconnect the flexible cable (SU11-SD11) and the bridge connectors (SC42-SD42 and SC46-SD46).
3. Remove the screws ($\times 2 \rightarrow$, $\times 1 \rightarrow$) and remove the SD-Board.




9.2.14. Remove the SC-Board

1. Unlock the tapes to free the cables.
2. Disconnect the connector (SC2).
3. Disconnect the flexible cable (SC20).
4. Remove the screws ($\times 7 \rightarrow$) and remove the SC-Board.




9.2.15. Work instructions for the Rubber sheet for SC-Board

1. Rubber sheets are put between the board and rear cover for EMC requirement and heat radiation. Confirm rubber sheets were placed at each portion when assembling as shown in figure.




9.2.16. Remove the SS-Board

1. Disconnect the connector (SS11).
2. Disconnect the flexible cable (SS33).
3. Disconnect the flexible cables (SS52 and SS54).
4. Remove the screws ($\times 5 \rightarrow$, $\times 3 \rightarrow$) and remove the SS-Board.




9.2.17. Work instructions for the Rubber sheet for SS-Board

1. Rubber sheets are put between the board and rear cover for EMC requirement and heat radiation. Confirm rubber sheets were placed at each portion when assembling as shown in figure.




9.2.18. Remove the SS2-Board

1. Disconnect the flexible cable (SS57).
2. Remove the screws ($\times 2 \rightarrow$) and remove the SS2-Board.




9.2.19. Remove the USB cable (A-WiFi)

1. Remove the screw ($\times 1 \rightarrow$).
2. Remove the USB cable (A-WiFi).




9.2.20. Remove the Metal bracket bottom

1. Remove the screws ($\times 4 \rightarrow$, $\times 2 \rightarrow$) and the Metal bracket bottom.




9.2.21. Remove the K-Board

1. Remove the screws ($\times 2 \rightarrow$) and remove the LED panel case.




2. Disconnect the connector (K10).
3. Remove the claw ($\times 1 \rightarrow$) and remove the K-Board.
4. Remove the LED panel.




9.2.22. Remove the Cabinet assy from the Plasma panel section


1. Place the Cabinet assy on a flat surface of a table (covered by a soft cloth) and a cushion.



2. Remove the screws ($\times 15 \rightarrow$).




3. Remove the Cabinet assy from the Plasma panel section.




9.2.23. Remove the Contact metals

1. Remove the screws ($\times 16 \rightarrow$).
2. Remove the Contact metal side (L, R).
3. Remove the screws ($\times 15 \rightarrow$).
4. Remove the Contact metal bottom.




9.2.24. Remove the C1-Board

1. Disconnect the flexible cables (CB1, CB2, CB3, CB4 and CB5).
2. Disconnect the flexible cable (C10).
3. Disconnect the connectors (C14 and C18).
4. Remove the screws ($\times 4 \rightarrow$) and remove the C1-Board.




9.2.25. Remove the C2-Board

1. Disconnect the flexible cables (CB6, CB7, CB8, CB9, CB10 and CB11).
2. Disconnect the flexible cables (C20, C21 and C26).
3. Disconnect the connectors (C25 and C28).
4. Remove the screws ($\times 6 \rightarrow$) and remove the C2-Board.



9.2.26. Remove the C3-Board


1. Disconnect the flexible cables (CB12, CB13, CB14 and CB15).
2. Disconnect the flexible cables (C31 and C36).
3. Remove the screws ($\times 4 \rightarrow$) and remove the C3-Board.



9.2.27. Replace the Plasma panel

Caution:

Place the Plasma panel on a flat surface of a table (covered by a soft cloth) and a cushion.



A new Plasma panel itself without Contact metals is fragile. To avoid the damage to new Plasma panel, carry a new Plasma panel taking hold of the Contact metals.

1. Place a carton box packed a new Plasma panel on the flat surface of the work bench.
2. Open a box and without taking a new Plasma panel.
3. Attach the Cabinet assy and each P.C.Board and so on, to the new Plasma panel.

10 Measurements and Adjustments

10.1. Adjustment

10.1.1. Vsus selection

Caution:

When Plasma panel or A-board is replaced, Vsus should be set to LOW or HIGH.


Procedure

1. Go into main item [VSUS] in Service Mode. LOW or HIGH will be displayed.
2. Press [OK] button to go to TEST stage.
White pattern without On-Screen Display will be displayed during TEST and CONF stage. Press [5] button to display the On-Screen Display.
3. Press [VOL (-)] button to set to LOW.
4. In LOW setting
 - a. If no several dead pixel is visible remarkably in white pattern, press [3] button to go to CONF stage.
 - b. If the several dead pixels are visible remarkably in white pattern, Set to HIGH by press [VOL (+)] button. Press [3] button to go to CONF stage if the symptom is improved.
5. Press [OK] button in CONF stage to store LOW or HIGH.
6. Exit Service Mode by pressing [Power] button.

Notes:

Do not overwrite because data is written in NAND Flash after executing adjustment of V-SUS Voltage.

Vsus selection in Service mode



10.1.2. White balance adjustment

Name of measuring instrument		Remarks
Color analyzer (Minolta CS-2000 or equivalent)		
Procedure		Remarks
1. Enter the Service mode. 2. Receive the Analog-RF (except for no signal) or set CVBS/YUV/HDMI (no signal is available). 3. Select [WB-ADJ] by using [1] and [2] key in the remote controller. 4. Check that the colour balance and the viewing mode is the values written in table1 and 2. 5. [INNER PATTERN] is displayed by using [5] key by using [5] key in the remote controller. 6. Select [G-CUTOFF] by using the [3] and [4] key in the remote controller, and set the value to [80] by using the volume [+] and [-] key. Also, [B-CUTOFF] and [R-CUTOFF] set to [80] 7. Set [G-DRIVE] value to the initial data (ex. D0). 8. Set the color analyzer and adjust color point to the values written in table1 by using [B-DRIVE] and [R-DRIVE] 9. Increase RGB-DRIVE value so that the maximum drive value of one of R-DRIVE or G-DRIVE or B-DRIVE should become [FF] ([ALL-DRIVE] set to [FF].)		

Table 1 : White Balance Target value


COOL		NORMAL		WARM	
x	y	x	y	x	y
0.267	0.269	0.288	0.296	0.313	0.326

Table2 : Setting of Viewing Mode


Colour Balance	Viewing Mode
Cool	Dynamic
Normal	Dynamic
Warm	Cinema

11 Block Diagram


11.1. Main Block Diagram




11.2. Block (1/4) Diagram




11.3. Block (2/4) Diagram



11.4. Block (3/4) Diagram



11.5. Block (4/4) Diagram



12 Wiring Connection Diagram

12.1. Caution statement.

Caution:


Please confirm that all flexible cables are assembled correctly.

Also make sure that they are locked in the connectors.


Verify by giving the flexible cables a very slight pull.

12.2. Wiring (1)

NOTE: ALIGN THE TAPE WITH MARKED LINES



12.3. Wiring (2)



12.4. Wiring (3)

